

The Admix Powder Induction Line-Up

Three models for all your ergonomic, high viscosity and shear requirements

<i>CAPABILITIES</i>	<i>OES-VPI™</i>	<i>PIC™ System</i>	<i>Fastfeed™</i>
<i>Maximum Viscosity</i>	<i>2500 CPS*</i>	<i>2500 CPS*</i>	<i>2500 CPS*</i>
<i>Maximum Percent Solids</i>	<i>78%</i>	<i>78%</i>	<i>78%</i>
<i>Average Powder Feed Rate</i>	<i>Up to 200# per minute</i>	<i>Up to 200# per minute</i>	<i>Up to 400# per minute</i>
<i>Variable Powder Feed Rate</i>	<i>Yes</i>	<i>Yes</i>	<i>Yes</i>
<i>Integral Shear</i>	<i>No</i>	<i>No</i>	<i>Yes</i>
<i>Integral Controls</i>	<i>No</i>	<i>Included</i>	<i>Included</i>
<i>Ergonomic Work Table</i>	<i>No</i>	<i>Included</i>	<i>Included</i>
<i>Sensitive to Changing Viscosities</i>	<i>No</i>	<i>No</i>	<i>No</i>
<i>Hopper Capacity</i>	<i>3.5 cu. ft.</i>	<i>3.5 cu. ft.</i>	<i>3.5 cu. ft.</i>

*Higher viscosities achievable with the addition of a positive displacement take-away pump

OES-VPI



Fastfeed Model FF-425

