



Powder Induction Equipment Line-Up

Several models are available for your ergonomic, viscosity and shear requirements.

CAPABILITIES	Optifeed EZ for Meat & Poultry	Optifeed OES-E200	Optifeed OES-V200	Optifeed OES-V250	PIC 200	PIC 250	Fastfeed 425	Fastfeed 575
Maximum Viscosity	500 CPS	200 CPS	2500 CPS	2500 CPS	2500 CPS	2500 CPS	2500 CPS	2500 CPS
Maximum % Solids	78%	25%	78%	78%	78%	78%	78%	78%
Powder Feed Rate	160 lbs. / 73 kg/min.	140 lbs. / 64 kg/min.	200 lbs. / 91 kg/min.	400 lbs. / 181 kg/min.	200 lbs. / 91 kg/min.	400 lbs. / 181 kg/min.	200 lbs. / 90 kg/min.	400 lbs. / 181 kg/min.
Variable Powder Feed Rate	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Integrated High Shear	No	No	No	No	No	No	Included	Included
Integrated Motor Controls	No	No	No	No	Included	Included	Included	Included
Ergonomic Worktable	No	No	No	No	Yes	Yes	Yes	Yes
Sensitive to Changing Viscosities	No	Yes	No	No	No	No	No	No
Hopper Capacity	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.	3.5 cu. Ft.
Pump Type	Vacuum	Eductor	Vacuum	Vacuum	Vacuum	Vacuum	Vacuum	Vacuum

Note: Higher viscosities achievable with the addition of a positive displacement take-away pump. Powder feed rates are typical for certain powders; rates depend on powder type and fitting sizes.

Fastfeed™



Optifeed™



PIC™

